

PIRANHA® HOSE PRODUCTS FOR HIGH PRESSURE WATER JETTING



SPECIFICATIONS & FEATURES:

	SLBU-08	LLRD-08	SHBK-08	LAGR-08
	Slick, non-binding cover for lower pressure applications	5,000 psi working pressure; high safety margin; resilient, longer lasting braid	4,000 psi working pressure; high safety margin; tight bend ratio	4,000 psi working pressure; crush, cut and abrasion resistant; tight bend ratio
*Nominal Inside Diameter (ID)	1/2"	1/2"	1/2"	1/2"
Nominal Outside Diameter (OD)	0.83"	0.80"	0.87"	1.00"
Maximum Operating Pressure	3,000 psi	5,000 psi	4,000 psi	4,000 psi
Minimum Burst/Safety Rating	7,500 psi	12,500 psi	12,000 psi	10,000 psi
Minimum bend radius (in.)	4"	4"	3"	3"
Weight per foot	0.16 lbs/ft	0.13 lbs/ft	0.20 lbs/ft	0.19 lbs/ft
Reinforcement Braid/Layers	Dual poly	Single aramid	Dual poly	Dual poly
*Other available sizes (ID)	08=1/2"; 10=5/8"; 12=3/4"; 16=1"	1/4"; 3/8"	5/8"	SAOR-10,12,16,20

All hoses are constructed with a polyolefin inner tube, high tensile synthetic braid reinforcement to reach recommended operating and specified minimum burst pressure ratings and covered with a high abrasion resistant polyether-urethane composite material.

Distributed by: **HARBEN California***

AMERICAN HYDRO-VAC EQUIPMENT CO., INC.

Call us: 949-515-3481 / Fax: 949-642-7745 / E-mail: sales@harbencalifornia.com

www.harbencalifornia.com

*Harben® is a registered trade mark of Flowplant Group, Ltd., the parent company of Harben, Inc. Harben California is an independent, authorized dealer & service center for Harben, Inc., operated by American Hydro-Vac Equipment Co., Inc.