

# PIRANHA HOSE PRODUCTS FOR HIGH PRESSURE WATER JETTING



## Features:

**BLUE:** Slick, non-binding cover.

For lower pressure applications

**RED:** 5,000 psi working

pressure; high safety margin

**BLACK:** Tight, 3" bend ratio;

high safety margin

### SLBU-08

\*Nominal ID: 1/2"

Nominal OD: 0.83"

Max. operating pressure: 3,000 psi

Min. burst pressure: 7,500 psi

Min. bend radius: 4-in.

Weight: 0.16 lbs./ft.

Dual poly braid reinforcement

\*Also available: 3/4" ID

### LLRD-08

\*Nominal ID: 1/2"

Nominal OD: 0.80"

Max. operating pressure: 5,000 psi

Min. burst pressure: 12,500 psi

Min. bend radius: 4-in.

Weight: 0.13 lbs./ft.

Single aramid braid

\*Also available: 1/4" & 3/8" ID

### SHBK-08

\*Nominal ID: 1/2"

Nominal OD: 0.87"

Max. operating pressure: 4,000 psi

Min. burst pressure: 12,000 psi

Min. bend ratio: 3-in.

Weight: 0.20 lbs./ft.

Dual poly braid

\*Also available: 5/8" ID

All hoses are constructed with a polyolefin inner tube, high tensile synthetic braid reinforcement to reach recommended operating and specified minimum burst pressure ratings and covered with a high abrasion resistant polyether-urethane composite material.

Distributed by:

**HARBEN** California\*

AMERICAN HYDRO-VAC EQUIPMENT CO., INC.

Call us: 949-515-3481 / Fax: 949-642-7745 / E-mail: sales@harbencalifornia.com

[www.harbencalifornia.com](http://www.harbencalifornia.com)

\*Harben® is a registered trade mark of Flowplant Group, Ltd., the parent company of Harben, Inc. Harben California is an independent, authorized dealer & service center for Harben, Inc., operated by American Hydro-Vac Equipment Co., Inc.