

THERMOPLASTIC HOSE PRODUCTS FOR HIGH PRESSURE WATER JETTING



BLUE: LLBU-08

Nominal ID: ½"

Nominal OD: 1.48"

Max. operating pressure: 3,000 psi

Min. burst pressure: 7,500 psi

Min. bend radius: 4-in.

Weight: 0.16 lbs./ft.

RED: LLRD-08

Nominal ID: ½"

Nominal OD: 0.80"

Max. operating pressure: 5,000 psi

Min. burst pressure: 12,500 psi

Min. bend radius: 4-in.

Weight: 0.13 lbs./ft.

BLACK: SHBK-08

Nominal ID: ½"

Nominal OD: 0.80"

Max. operating pressure: 4,000 psi

Min. burst pressure: 12,000 psi

Min. bend ratio: 3-in.

Weight: 0.20 lbs./ft.

All hoses are constructed with a polyolefin inner tube, high tensile synthetic braid reinforcement to reach recommended operating and specified minimum burst pressure ratings, then covered with a high abrasion resistant polyether-urethane cover.

Distributed by:

HARBEN California*

AMERICAN HYDRO-VAC EQUIPMENT CO., INC.

Call us: 949-515-3481 / Fax: 949-642-7745 / E-mail: sales@harbencalifornia.com

www.harbencalifornia.com

*Harben® is a registered trade mark of Flowplant Group, Ltd., the parent company of Harben, Inc. Harben California is an independent, authorized dealer & service center for Harben, Inc., operated by American Hydro-Vac Equipment Co., Inc.